

Auto / Semi-Auto Espresso Machines



Classic Series Espresso Machines

Easy Espresso



Model CS2-220

- Elegant design combines a metallic curved front with diamond black sides.
- Pressure gauge/sight glass allows easy monitoring.
- Separate independent auto back flushing allows convenient machine maintenance.
- Stainless steel exchange boiler provides temperature stability.
- Hot water and steam knob features two easy-to-use methods of operation.
- Steam pressure release function ensures safe operation.
- Boiler low water safety feature prevents machine from overheating without water.
- Hot water dispensing wand.
- Raised group heads fits tall, take-away cups.



Model CS1-110



Model	Number of Heads	Boiler Size	Electrical	Product Dimensions (H x W x D)	Ship Weight
CS1-110 (1008-000)	1 Group	6 qts.	110/120V / 2 kW / 18A / 1 Ph	25" x 19" x 20.5"	104 lbs.
CS1-220 (1008-001)	1 Group	6 qts.	220/240V / 2 kW / 10A / 1 Ph	25" x 19" x 20.5"	104 lbs.
CS2-220 (1008-002)	2 Groups	13 qts.	220/240V / 4.7 kW / 20A / 1 Ph	25" x 28" x 20.5"	115 lbs.
CS3-220 (1008-003)	3 Groups	19 qts.	220/240V / 6.5 kW / 27A / 1 Ph	25" x 37" x 20.5"	148 lbs.

Plumbing: Unit attaches to 0.75" hose connection, 0.5" water line required. Water pressure between 20 PSI and 120 PSI. Use regulator for higher pressure.

Note: 4" clearance required on side and rear.



GRINDMASTER®