



MODELS

KGH-OF-(30, 40, 50, 60, 80, 100)-S KGH-OF-(30, 40, 50, 60, 80, 100)-R GRAB-N-GO HIGH PROFILE CASE

CASE HOLDS 36°F TO 40°F • FORCED AIR REFRIGERATION • OPEN FRONT FRONT LOADING • LED LIGHTING IN CANOPY AND UNDER SHELVES PULL DOWN NIGHT CURTAIN • CASES CAN BE MULTIPLEXED













SELF CONTAINED	Model	O.A. Length (inches)	Volume FT³	Electrical						Weight lbs		Crate Size (inches)			
				Compressor			LIGHTS	Evap	Total	Total	No	With			
				Н.Р	F.L.A 115V	F.L.A 230V	Fans HTRS	PAN	Amps 115 V	Amps 230 V	Crate	Crate	L"	W″	H″
	KGH-OF-30-S	29.2	15.9	3/4	16.0	N/A	1.40	3.3	20.7	N/A	408	542	32.2	32.5	85.4
	KGH-OF-40-S	41	23.3	1	16.2	N/A	1.80	8.3	26.3	N/A	463	633	44	32.5	85.4
	KGH-OF-50-S	50.2	29.1	1	16.2	N/A	2.40	8.3	27.0	N/A	514	728	53.2	32.5	85.4
	KGH-OF-60-S	60.6	35.6	1-1/4	N/A	9.2	2.46	8.3	10.8	9.2	580	818	63.6	32.5	85.4
	KGH-OF-80-S	78.2	46.6	2 x 1	N/A	2 x 8.2	2.91	8.3	11.2	16.4	752	1049	81.2	32.5	85.4
	KGH-OF-100-S	96.6	58.2	2 x 1	2 x 16.2	N/A	2 x 2.4	2 x 8.3	2 x 27	N/A	939	1285	99.6	32.5	85.4

		O.A.			Weight bs		
	Model	Length (inches)	115 Volts Total Amps	B.T.U	No Crate	With Crate	
#	KGH-OF-30-R	29.2	0.85	4793	342	476	
REMOTE	KGH-OF-40-R	41	0.90	6940	353	523	
22	KGH-OF-50-R	50.2	1.30	7565	404	617	
	KGH-OF-60-R	60.6	1.36	9383	463	701	
	KGH-OF-80-R	78.2	1.81	13881	562	860	
	KGH-OF-100-R	96.6	2.60	14921	691	1043	

STANDARD FEATURES

Tempered side glass

CFC free injected foam insulation

Silver colored PVC coated steel front panel

PVC coated steel gray interior

Black steel kick plate

Foamed polystyrene black end panels

Height adjustable shelves can be tilted

Products stop on all shelves

Temperature and defrost regulated by a digital controller

Removable condensate evaporating pan for easy cleaning on

self contained units

Slide out condensing unit on self-contained units

Digital thermometer

Levelling feet

OPTIONAL FEATURES

Stainless steel interior and / or exterior

Other colors available

Solid or full view end panels

Additional shelves

Joining Kit

Partition and or / product dividers

Price tag molding

Condensate evaporating pan for remote cases

Casters add 4-3/8" to height


Stainless steel legs are adjustable from 5-1/8" to 7-5/8"

One year parts and labor with an additional four years on the compressor (part only)

Tel: 786.600.4687 / Toll Free: 844.218.8477
Fax: 786.661.4100



Tel: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / toll free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com





Levellina Feet

Adjustable Legs

Optional Mounting

NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R404a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-1/2° each. Ventilation grills at front and back cannot be blocked. B.T.U.S are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle. On remote cases, if no floor drain is provided, a condensate evaporating pan must be ordered and 3.3 or 8.3 amps added to the amp load. Remote cases must be hard wired – no plugs.



Hydra - Kool is a registered trademark of MVP Group Corp. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE