

## **BOTTOM-MOUNTED REACH-IN DUAL TEMPERATURE REFRIGERATORS**



Toll Free Number: 1 (800) 931-8628



Email: Info@dukersusa.com



Website: www.dukersusa.com

## MODEL: D83RF

## Features and Benefits

- \* High Resistance to dust, high quality condenser
- \* R290 Natrual Refrigerant, promotes faster cool down and efficient energy consumption
- \* 3-year parts and labor, 5-year compressor warranty
- \* Stainless steel inside and outside, sealed interior floors and rounder cabinet corners for easy cleaning
- \* Self-closing doors with stay open feature.
- \* Adjustable, heavy duty shelves

### Technical Specifications

Voltage/Frequency	115V/60Hz		
Refrigerant	R290		
Type of Defrost	Automatic		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel		
Net Weight	595 lbs		
Total Capacity	64.80 cu ft		
Total Current	8.6A/16A		
Climatic Category	4/5		
Nema Config.	5-20P		











MODEL NO	TEMPERATURE RANGE ( °F )	EXTERNAL DIMENSION WXDXH(INCHES)	PACKING, CARTON WXDXH (INCHES)	DOOR	40GP CONTAINER CERTIFICATION
D83RF	33 ~ 41 °F -8°F ~ -0°F	82%" X 325%" X 80%"	84¼" X 34¼" X 84¾"	3	13

# BOTTOM-MOUNTED REACH-IN DUAL TEMPERATURE REFRIGERATOR

## MODEL: D83RF

Model: D83RF

Rated Voltage: 115V AC

Rated Frequency: 60Hz

Total Input Power: 760W/1300W

Total Current: 8.6A/16A

Total Capacity: 64.80 cu ft

Refrigerant: R290/5.22 oz

Climatic Category: 4/5

Protection Type I

Design pressure High Side :300PSIG

Low Side:150PSIG

Insulation Blowing Gas C-pentane

Net Weight: 595 lbs

NEMA Config 5-20P

#### STANDARD FEATURES

#### **BOTTOM MOUNT COMPRESSOR**

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy service

#### HIGH QUALITY STEEL

Interior and exterior high quality steel minimizes dents, scratches and rust

## HIGH DENSITY POLYURETHANE INSULATION CFC

free and high density cell foam is Eco-friendly and more energy efficient

#### STURDY, CLEAN STAINLESS SHELVING

High quality coated stainless shelves may prevent peel and rust.

#### SELF-CLOSING DOOR SYSTEM

Door Automatically close at 60°


REFRIGERATORS HOLDS 33 °F - 41 °F


FOR BEST IN REFRIGERATORS FREEZER HOLDS -8°F ~ -0°F

FOR BEST IN FREEZER

NEMA 5-20P 115/60/1

#### **PLAN VIEW**







**FRONT VIEW** 

California Office 2488 Peck Road, City of Industry, CA 90601 (562) 568-4060 www.dukersusa.com New Jersey Office 475 S Clinton Ave South Plainfield, NJ 07080 (800) 608-9289 Info@dukersusa.com

Georgia Office 6513 Warren Dr NW Norcross, GA 30093 (678) 580-3960 service@dukersusa.com Texas Office 1444 N Cockrell Hill Rd #104 Dallas, TX 75211 (469) 421-1040 Warrenrty@dukersusa.com