

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

U19F 29" Single Solid Door Narrow Depth Reach-In Freezer



FEATURES

- ▶ Stainless steel exterior and interior
- ▶ Aluminum back
- ▶ Narrow Depth
- ▶ Refrigeration system keeps food at safe temperatures
- ▶ Self-closing doors with 90 degree stay-open feature
- ▶ Locks and keys included
- ▶ Adjustable heavy-duty PVC coated shelves
- ▶ Recessed door handle
- ▶ Electronic control system
- ▶ Preinstalled heavy-duty casters with brakes
- ▶ Removable installation board
- ▶ Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

▶ cETLus Listed
 ▶ ETL Sanitation Listed
 Conforms to UL & NSF Standards



US Restaurant Group is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	29"W x 25.4"D x 81.5"H
Interior Dimensions	24.4"W x 20.4"D x 60.3"H
Packaging Dimensions	30.3"W x 27.5"D x 85.5"H
Net Volume	19 cu. ft.
Unit Weight	282 lb.
Shipping Weight	308 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	8.28
Plug Type	NEMA 5-15P
Power Cord Length	96"

COOLING

Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/2+

CONSTRUCTION

Exterior Material	304 Stainless Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	3 Qty: 23.4"W x 19.4"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

DIAGRAM

MODEL:U19F

MFR MODEL:U-19F-HC



NEMA 5-15P

