GAS CHICKEN ROTISSERIES















FRG2VE / FRG4VE FRG6VE / FRG8VE

Standard Features

- All Stainless-Steel construction
- Sliding tempered glass doors
- Stainless-Steel V skewers, no hook required.
- 2 Stainless-Steel grease drawer collectors
- FRG4VE and FRG6VE 3" casters included
- FRG2VE and FRG8VE legs included
- Independent motor per spit
- Motor rotation 2 rpm
- Capacity 5 chickens or 40 lbs. per spit
- Cooking time 50 to 60 min (calculated with 4 lbs. birds)







FRG2VE

GAS CHICKEN ROTISSERIES















Easy, clean, no tools required, secure, quick load and unload chickens

H W

Accessories:

- RMET209 Skewers round bar with wood handle for hooks
- RMET010 Double Stainless-Steel hook.
- RMET011 Single Stainless-Steel hook.



SPECIFICATIONS				
	FRG2VE	FRG4VE	FRG6VE	FRG8VE
Chickens Capacity	10	20	30	40
Spit Qty	2	4	5	8
Burners Qty	1	2	3	4
Gas Power (BTU)	30,000	60,000	90,000	120,000
Gas connection	3/8" flare	1/2" NPT	1/2" NPT	1/2" NPT
Power Supply	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph
Amps	1.2	1.8	3.6	4.8
Plug / Connection	Nema 15-5	Nema 15-5	Nema 15-5	Nema 15-5
External Dim WxDxH	46" x 24" x 31"	46" x 24" x 58"	46" x 24" x 65"	46" x 24" x 70"
Weight (lbs)	137	227	271	302
Shipping Dim WxDxH	47" x 25" x 32"	47" x 25" x 59"	47" x 25" x 66"	47" x 25" x 75"
Shipping Weight (lbs)	167	267	271	302



Notes:

- At least a 5" clearance is needed on oven's rear, left and right side for proper performance.
- Ovens are top-vented, operated under a hood or direct exhaust (where permitted)

