ELECTRIC CHICKEN ROTISSERIES







- All Stainless-Steel construction
- Sliding tempered glass doors
- Stainless-Steel V skewers, no hook required
- 2 Stainless-Steel grease drawer collectors
- FRE4VE and FRE6VE 3" casters included
- FRE2VE and FRE8VE legs included
- Independent motor per spit
- Motor rotation 2 rpm
- Capacity 5 chickens or 40 lbs. per spit
- Cooking time 50 to 60 min (calculated with 4 lbs. birds)

	FRE2VE	SPECIFICATIONS FRE4VE	FRE6VE	FRE8VE
Chickens capacity	10	20	30	40
Voltage	220V/50-60hz/1ph	220V/50-60hz/1ph	220V/50-60hz/1ph	220V/50-60hz/ 3-1ph (field convertible)
Plug	No plug	No plug	No plug	No plug
Amps	16	32	50	1ph - 64 3ph -38
Power (Watts)	3,000	6,000	9,000	12,000
External Dim WxDxH (inch)	46x24x31	46x24x58	46x24x65	46x24x70
Weight (lbs)	137	227	271	302
Shipping Dim WxDxH	47x25x32	47x25x59	47x25x66	47x25x75
Shipping Weight (Ibs)	167	267	271	302

Ovens equipped only with V spit skewers

Easy, clean, no tools required, secure, quick load and unload chickens



AMPTO

Installation Notes:

- At least a 5" clearance is needed on oven's rear, left and right side for proper performance.
- Ovens are top-vented, operated under a hood or direct exhaust (where permitted)
- All electric units required a 220V with a neutral connection