

## F99EKDPS

### UNDERCOUNTER DISHWASHER

- Soft start
- Soap and rinse pumps
- Automatic tank loading
- Stainless steel construction 18/10 AISI 304
- Stainless Steel upper and lower rotating wash and rinse arms
- Removable control panel for easy maintenance
- Double wall thermal and acoustic insulation
- Self-washing slanted tank with rounded edges
- (2) Integral tank filters in stainless steel
- Counterbalanced double-wall door




SPECIFICATIONS	F99DYPS
POWER	6500W, 208 V1ph 60Hz, 35A
RINSE-AID DISPENSER	YES
DETERGENT PUMP	YES
CLEARANCE	14,57"
RACK DIMENSIONS (L x W)	19,68" x 19,68"
WORK HEIGHT	12,40"
TANK CAPACITY	4,76 Gal
DIMENSIONS (L x W x H)	23,62" x 25,59" x 32,28"
WASH CYCLE DURATION	2-3-4 mins
WASH CYCLE CAPACITY	30/20/15 baskets/hr
WATER CONSUMPTION	0,6 Gal
ELECTRIC PUMP	650 W
WASH TANK ELEMENT	2000 W
RINSE TANK ELEMENT	6000 W
BOILER CAPACITY	1,58 Gal
WATER INLET TEMPERATURE	55±60°C/131±140°F
WATER INLET CONNECTION	3/4"
WATER OUTLET CONNECTION	3/4"
INLET WATER PRESSURE	40±80 psi
WATER HARDNESS	7,2±12,5 °f
RINSE TEMPERATURE	82±90°C/180±195°F
NET WEIGHT	159 lbs
SHIP DIMENSIONS (L x W x H)	25,10"x29,15"x34,36"
SHIP WEIGHT	181 lbs
NOISE LEVEL	<54dB(A)

### INCREASED CLEARANCE


The clearance height is increased by 1.6" compared to the previous model. It is now 14.57", allowing larger items to fit.

### NEW MICROFILTER PLUS

The new microfilter system keeps water clean for longer, and reduces detergent consumption by 20%. The fine residual dirt is collected and discharged also during the washing cycle.



CLEARANCE



OPTION: CLEARANCE FOR DOUBLE SLIDE

