

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

CBB-48G-SL 48" Narrow Depth Black Sliding Glass Door Back Bar Cooler



FEATURES

- Durable S/S top, interior walls, floor and ceiling
- Vinyl on steel in black finish exterior
- Refrigeration system keeps food at safe temperatures
- Electronic control system
- Adjustable heavy-duty PVC coated shelves
- Self-closing doors with locks
- Sliding doors
- Narrow depth
- LED interior lighting
- Removable installation board
- Hydro-Carbon R290 refrigerant

This Coldline commercial back bar cooler is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	48.8"W x 24.4"D x 35.6"H
Interior Dimensions	36.25"W x 18.5"D x 28.9"H
Packaging Dimensions	51.25"W x 27.5"D x 41.75"H
Working Height	35.3"
Product Capacity	(2) ½ kegs
Net Volume	13 cu. ft.
Unit Weight	231 lb.
Shipping Weight	282 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.88
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/5

CONSTRUCTION

Exterior Material	Coated Steel
Exterior Color	Black
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Sliding
Door Type	Glass
Depth Style	Narrow
Shelf Size	(4) Qty: 17.6"W x 18.1"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D

TECHNICAL DRAWING

MODEL: CBB-48G-SL

MFR ITEM #:



NEMA 5-15P

