

Vertical Contact Toaster | VCT



VCT-2000



with wide mouth
bun feeder



with motorized
butter wheel and
bun feeder



with heated base

For more than 25 years, the Vertical Contact Toaster has been a staple in foodservice operations, building a reputation for quality, performance, and reliability throughout the world.

The Vertical Contact Toaster gives buns a consistent, golden brown finish so they don't soak up the juices of the ingredients, helping the sandwich stay firm and delicious. With a dual-sided platen, the Vertical Contact Toaster has more capacity than conventional single-sided toasters, allowing operations to quickly serve fresh products to customers without making them wait.

The VCT-2000 features a digital controller for making precise adjustments to the quality of the toast for different bread products. A built-in auxiliary heater warms the top sides of the buns to help keep the assembled sandwich warmer for longer.

The VCT-2000 also includes belt wraps to minimize bun marking. Available features for the unit include a wide mouth bun feeder, motorized butter wheel, heated base, and back plate.

FEATURES

- Dual-sided platen for additional toasting capacity compared to conventional single-sided toasters.
- Auxiliary heater warms top side of buns.
- Digital controller to adjust temperature of the platen.
- Space-saving vertical design.
- Continuously moving conveyor for immediate toasting.
- Separate compression adjustments for the heel and the crown.
- Release sheets allow buns to move easily down the heated platen without sticking or slipping.
- Easy to operate and clean.
- Stainless steel construction.
- Available toasting times range from 10 to 28 seconds.
- Additional features available, including wide mouth bun feeder, butter wheel, and heated base.

Vertical Contact Toaster | VCT

Dimensions

| Model & Mfg. No. | Width (A) | Depth (B) | Height (C) |
|------------------|-----------|-----------|------------|
| VCT-2000 | | | |
| 9210100 | | | |
| 9210114 | 21 1/4" | 15 1/4" | 23 1/4" |
| 9210118 | (540 mm) | (387 mm) | (591 mm) |
| 9210200 | | | |
| 9210224 | | | |
| VCT-2000 | | | |
| 9210116 | | | |
| 9210121 | 21 1/4" | 15 1/4" | 24 1/4" |
| 9210123 | (540 mm) | (387 mm) | (616 mm) |
| 9210203 | | | |
| 9210212 | | | |
| VCT-2000 | | | |
| 9210300 | | | |
| 9210304 | 21 1/4" | 10 3/4" | 23 1/4" |
| 9210400 | (540 mm) | (273 mm) | (591 mm) |
| 9210402 | | | |

Shipping Dimensions

| Model & Mfg. No. | Height | Width | Depth | Weight |
|------------------|----------|----------|----------|---------|
| VCT-2000 | | | | |
| 9210116 | | | | |
| 9210121 | 33" | 26" | 16" | 88 lbs. |
| 9210123 | (838 mm) | (660 mm) | (406 mm) | (40 kg) |
| 9210203 | | | | |
| 9210212 | | | | |
| VCT-2000 | | | | |
| 9210100 | | | | |
| 9210114 | | | | |
| 9210118 | | | | |
| 9210200 | 24" | 22" | 15" | 75 lbs. |
| 9210224 | (610 mm) | (559 mm) | (381 mm) | (34 kg) |
| 9210300 | | | | |
| 9210304 | | | | |
| 9210400 | | | | |
| 9210402 | | | | |

Bun Specifications

| Model & Mfg. No. | Feeder Opening | Crowns | | Heels | |
|------------------|----------------|---------|---------|---------|---------|
| | | Min. | Max. | Min. | Max. |
| VCT-2000 | | | | | |
| 9210100 | | | | | |
| 9210114 | | | | | |
| 9210118 | | | | | |
| 9210200 | 1 3/4" | 1/2" | 7/8" | 1/2" | 7/8" |
| 9210300 | (44 mm) | (13 mm) | (22 mm) | (13 mm) | (22 mm) |
| 9210304 | | | | | |
| 9210400 | | | | | |
| 9210402 | | | | | |
| VCT-2000 | | | | | |
| 9210116 | | | | | |
| 9210121 | | | | | |
| 9210123 | 1 3/4" | 3/4" | 1 1/8" | 5/8" | 1" |
| 9210203 | (44 mm) | (19 mm) | (29 mm) | (16 mm) | (25 mm) |
| 9210212 | | | | | |
| 9210224 | | | | | |

Specifications

| Model & Mfg. No. | Pass Through Time | Volts | Watts | Amps | Hertz | Plug Description |
|------------------------------------------------------------|-------------------|---------|-----------|-----------|-------|----------------------------------------------|
| VCT-2000 | | | | | | |
| VCT-2000 | | | | | | |
| 9210100 | 10 sec. | 208 | 3201 | 15.8 | 50/60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210200 | 10 sec. | 220-240 | 3019-3593 | 13.7-15 | 50 | CEE 7/7 16 Amp., 250 Volt |
| VCT-2000 with Wide Mouth | | | | | | |
| VCT-2000 | | | | | | |
| 9210116 | 10 sec. | 208 | 3291 | 15.8 | 60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210121 | 17 sec. | 208 | 3291 | 15.8 | 60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210123 | 28 sec. | 208 | 3291 | 15.8 | 60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210203 | 17 sec. | 220-240 | 3019-3593 | 13.7-15 | 50 | CEE 7/7 16 Amp., 250 Volt |
| VCT-2000 | | | | | | |
| 9210212 | 10 sec. | 220-240 | 3019-3593 | 13.7-15 | 50 | CEE 7/7 16 Amp., 250 Volt |
| VCT-2000 with Motorized Butter Wheel | | | | | | |
| VCT-2000 | | | | | | |
| 9210114 | 10 sec. | 208 | 3291 | 15.8 | 50/60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210118 | 17 sec. | 208 | 3291 | 15.8 | 50/60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 with Wide Mouth and Motorized Butter Wheel | | | | | | |
| VCT-2000 | | | | | | |
| 9210224 | 10 sec. | 220-240 | 3019-3593 | 13.7-15 | 50 | IEC-309 16 Amp., 230 Volt Pin & Sleeve |
| VCT-2000 with Heated Base | | | | | | |
| VCT-2000 | | | | | | |
| 9210300 | 10 sec. | 208 | 3326 | 16 | 50/60 | NEMA 6-20P 20 Amp, 250 Volt |
| VCT-2000 | | | | | | |
| 9210400 | 10 sec. | 220-240 | 3058-3640 | 13.9-15.2 | 50/60 | CEE 7/7 16 Amp., 250 Volt IEC-309 |
| VCT-2000 | | | | | | |
| 9210402 | 10 sec. | 220-240 | 3058-3640 | 13.9-15.2 | 50/60 | 16 Amp., 230 Volt Pin & Sleeve |
| VCT-2000 with Heated Base and Back Plate | | | | | | |
| VCT-2000 | | | | | | |
| 9210304 | 10 sec. | 208 | 3326 | 16 | 50/60 | NEMA 6-20P 20 Amp, 250 Volt |

Accessories

Bun Feeder (P/N 7000236): An automatic gravity-fed bun feeder.

Bun Feeder (P/N 7000787): An automatic gravity-fed bun feeder for use in wide-mouth toasters.

Butter Wheel (P/N 7000238): Stainless steel butter wheel and pan.

Butter Wheel (P/N 7000703): Stainless steel butter wheel and pan for use in wide-mouth toasters.

Low-Profile Bun Feeder (P/N 7000292): Low profile bun feeder allows for quick and easy loading of buns into the toaster.

P/N 1020231 05/17



Antunes delivers a complete range of countertop cooking equipment and water filtration solutions to foodservice operations around the world. Learn more about Antunes and its products at www.antunes.com.

Corporate Headquarters

Carol Stream, Illinois
Phone: (630) 784-1000
Toll Free: (800) 253-2991
Fax: (630) 784-1650

China Facility

Suzhou, China
Phone: 86-512-6841-3637
Fax: 86-512-6841-3907